



Round cable entry M40 with membrane for non-assembled cables, Mounting type: Snap-in and Screw, Length: 51 mm, Width: 51 mm, IP66, Colour: Grey

RAL: 7032

Business data

Article number	28915.6	
Article name	KES-R M40/8 GR	
GTIN (EAN)		
Packaging unit	10	
Quantity unit	PC	
Weight per piece (not including packaging)	10.8 g	
Weight per piece (including packaging)	10.8 g	
Unit of weight	G	
Customs number	39259020	
Country of origin	DE	
Product description	Cable Entry	
Colour	Grey	

Data sheet



28915.6 KES-R M40/8 GR


Technical data	
Further technical data	
Degree of protection for screw mounting	IP66
Wall thickness with lock nut mounting, max.	11 mm
Wall thickness with snap-in mounting, max.	2,5 mm
Mounting type	Snap-on and screw-on
Degree of protection	IP66
Min wall thickness	1 mm
Number of wires	8
Degree of protection for snap-in mounting	IP54
Dimensions	
Length	51 mm
Width	51 mm
Installation height	8 mm
Materials	
Material	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	80 °C
Sealing material	TPE
Halogen-free	✓
Silicone-free	✓
Environmental Product Compliance	
REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Data sheet 28915.6 KES-R M40/8 GR



Media







Data sheet 28915.6 KES-R M40/8 GR



Accessories

Locknuts

Hex. nut, Thread type: metric, Thread size: 40 mm, Material: Polyamide, Colour: Light grey



Article number	Article name	GTIN (EAN)	Packaging unit
4145.2	S/M 40x1,5 GR	4044211114268	50