

# Data sheet

## 3846.0 PZD 16/R



Crimping tool for crimping ferrules with and without plastic collars. Cross section range: 0.08-16 mm<sup>2</sup> (AWG 28-5). Easy to use, forced lock for correct, complete crimping, conductor entry can be rotated in 45° steps, self-opening thanks to built-in spring.

### Business data

Article number	3846.0
Article name	PZD 16/R
GTIN (EAN)	4044211236984
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	418 g
Weight per piece (including packaging)	466 g
Unit of weight	G
Customs number	82032000
Country of origin	DE
Product description	Crimping tool
Colour	Black / Grey

**Technical data**

**Application**

Wire-end TWIN-ferrule cross-section, max.	2 x 0,25 mm <sup>2</sup>
Wire-end TWIN-ferrule cross-section, min.	2 x 10,0 mm <sup>2</sup>
Crimp shape	Square crimp
Crimping range, min.	0.08 mm <sup>2</sup>
Crimping range, max.	16 mm <sup>2</sup>
Crimping range AWG, min.	28
Crimping range AWG, max.	5
Wire-end ferrule cross-section, min.	0.08 mm <sup>2</sup>
Max wire-end ferrule cross-section	16 mm <sup>2</sup>

**Dimensions**

Length	193 mm
Width	24 mm
Height	62 mm

**Environmental Product Compliance**

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

**Media**



Accessories

Crimp inserts



Crimping tool for crimping ferrules with and without plastic collars. Cross section range: 0.08-16 mm² (AWG 28-5). Wire entry can be rotated in 45° steps.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3845.0</u>	Insert PZU 16/R	4044211236991	1 ST



Crimping tool for crimping ferrules with and without plastic collars. Cross section range: 0.08-16 mm² (AWG 28-5). Wire entry can be rotated in 45° steps.

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3847.0</u>	Insert PZD 16/R	4044211237004	1 ST