


Data sheet

5408.2 RM-S/1S/24V DC/AC



Compact relay module, Screw connection, 1 NO contact, Soldered, Input voltage: 24 VAC/DC

Business data

Article number	5408.2
Article name	RM-S/1S/24V DC/AC
GTIN (EAN)	4044211067878
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	25.2 g
Weight per piece (including packaging)	29.3 g
Unit of weight	G
Customs number	85364900
Country of origin	NL
Product description	Relay module

Technical data

Dimensions

Length	77 mm
Width	11.2 mm
Height	55 mm

Ratings

Overvoltage category	III
Contamination degree	2

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.08 mm ²
Wire cross-section single-core (rigid), max.	4 mm ²
Wire cross-section stranded, min.	0.2 mm ²
Wire cross-section stranded, max.	2.5 mm ²
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm ²
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm ²
Stripping length	7 mm
Torque	0.6 Nm

Input data

Input voltage	24 VAC/DC
Number of channels	1
Power consumption	0,6 W

Output data

Switching voltage / switching voltage max.	250 / 250 VAC
Continuous current max. / Inrush current max.	6 / 8 A
Contact configuration	1 NO contact
Switching capacity, max.	2000 VA
Electrical lifespan (AC1)	1,5x10 ⁵
Mechanical lifespan	10x10 ⁶

Materials

Contact material	AgNi 90/10
Working temperature, min.	-20 °C
Working temperature, max.	55 °C

Technical data

Further technical data

Protection class	IP20
Insulation voltage coil/contact	4 kV
Response/release time	9 / 7 ms

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Approvals

Standards and regulations



CE compliant	yes
Standards / specifications	DIN VDE 0110 / EN 50178

Data sheet

5408.2 RM-S/1S/24V DC/AC



Media



Accessories
