

G4 solid-state relay Opto 22, pluggable, LED display, 5x20 micro-fuse, Input voltage: 5 VAC

Business data

Article number	5977.0
Article name	G 4 OAC 5 A
GTIN (EAN)	4044211070946
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	26.4 g
Weight per piece (including packaging)	26.4 g
Unit of weight	G
Customs number	85365003
Country of origin	US
Product description	Solid-state relay

Technical data

Input data

Input voltage	5 VDC
Drop-out voltage	1 VDC
Control current	12 mA
Number of channels	1
Operating range	2,5-8 VDC
Switch-on threshold U/I	2,5 V / -

Output data

Output voltage range	24-280 VAC V
Voltage drop at 20 °C and rated current, max.	1,6 V
Continuous current max. / Inrush current max.	3 (@45°C) / 80 A

Materials

Working temperature, min.	-30 °C
Working temperature, max.	70 °C


Further technical data

Status display	✓
Response/release time	<0,5 Periode ms
Remarks	1 NO contact
Test voltage	4 kV

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2024-01-23
REACH Candidate Substance Note	No
RoHS Conform	yes

Media



Accessories
